

## Key Benefits

- 24 Gigabit PoE ports
- 4 fiber-capable ports
- Full remote management through web browser, console serial cable (CLI), or Telnet
- Each of the 24 ports can provide 15.4 Watts
- Remote power-cycling per port for rebooting unresponsive devices
- Heavy-duty metal 1U housing with rack mount hardware included
- Clean front face with cables in the back
- Quiet operation
- 802.1q: supports VLAN tagging
- 802.1p: supports Quality of Service
- Auto-detect powered devices and power consumption levels
- Stackable

# S24P

## 24-PORT GIGABIT SWITCH WITH 24 FULL PoE PORTS

The S24P is an Enterprise-Class, managed Gigabit switch equipped with 24 full PoE ports. This switch is ideal for powering audio/video devices which require Gigabit PoE, such as HDMI over IP transmitters, high bandwidth wireless access points, and high resolution IP cameras.



With its massive 390 Watt power supply, the S24P can provide Ethernet and power to devices that are 802.3af-compliant. Each of the 24 ports can deliver up to a full 15.4 Watts of power. In addition, each port can be power-cycled individually if a connected PoE device becomes unresponsive or needs to be rebooted.

The switch is fully managed and can be configured by web browser, CLI, or Telnet. It is also equipped with four fiber-capable ports that can support either RJ45 or SFP connectors. To support audio/video bridging, it features 802.1q (VLAN) and 802.1p (Quality of Service). Now, PoE devices that are connected to the S24P can pass and receive VLAN tags and control Quality of Service for reliable audio and video streaming.

The S24P is housed in a heavy-duty 1U metal housing with rack mount hardware included. All cables install from the rear, giving the switch a clean front face. Finally, even though the switch is capable of delivering 390 Watts of power to 24 separate PoE devices, it has extremely quiet fans, a key feature when installed in an audio/video rack.

HTTP://  
WWW.  
PAKEDGE  
.COM

1163 Triton Drive  
Foster City, CA 94404  
Main: 877.274.6100  
Fax: 650.685.5520  
sales@pakedge.com

**pakedgedevice&software inc.**

## S24P SPECIFICATIONS

### SUMMARY

Fixed port	20 10/100/1000Base-TX ports 4 Combo ports (10/100/1000Base-T or 1000Base-X) 1 Console port
LED Indicators	PWR, PoE, 1000M and Link/Act LED
Input voltage	100V-240V AC, 50/60Hz
Power consumption	390W (370W for PoE)
Operating temperature	0-40°C
Storage temperature	-10-70°C
Relative humidity	20%-85% (non-condensing)
Thermal methods	Built-in Noiseless Fan
<b>PoE</b>	
PoE port	24, 10/100/1000Base-TX ports
PoE Standard	IEEE802.3af, per port 15.4W
Pin assignment	V+ (RJ45 Pin 1, 2), V- (RJ45 Pin 3, 6)
PoE management	Support Port-base PoE status view and control
<b>Layer 2 Switching</b>	
Switching capacity	64G
MAC address table	8K, Support MAC address table management
MAC Address Binding	Support
MAC Address Filtering	Support
MAC Address Learning control	Control number of port-based MAC address learning
Jumbo Frame	Jumbo packets up to 16379 bytes
Port Feature	Port Control Port Isolation. Port Self-loop Detection
Port Mirroring	Support
VLAN	4K 802.1q VLANs, Support Ingress filter
Link Aggregation	Up to 8 maximum aggregation groups, each containing up to 8 GE ports
Traffic control	IEEE 802.3x full-duplex flow control
Rate Limit	Unit: 64kbps
Spanning Tree	IEEE 802.1s Multiple Spanning Tree Protocol (MSTP)
Ring Protocol	Support EAPS
Multicast	Support 256 Multicast groups Support IGMP Snooping
<b>Layer 3 Switching</b>	
Static ARP	Support
Static Routing	Support
L3 VLAN interface	Up to 32 L3 VLAN Interface
<b>Convergence</b>	
QoS	4 output queues on each port Support flexible queue scheduling algorithms: WRR, Q+WRR Support port-based / MAC-based / 802.1p / DSCP classification
<b>Security</b>	
Security Features	Support MAC-based 802.1X authentication Support AAA/RADIUS authentication Support WEB/Telnet password protection Support Accessing privilege mode password protection Support CPU Self-protection
Self-protection	Support CPU Self-protection
<b>Management</b>	
CLI	Support CLI (Commend Line Interface) configuration mode
Console	Support Configuration via the console port
Telnet	Support Local/remote configuration via Telnet
WEB	Support WEB management system
SNMP	Support System configuration with SNMP v1/v2/v3
User Management	Support Multi-user management
System Log	Support
Configuration File Download/Upload	Support Download/Upload configuration File via WEB/TFTP
Upgrade Firmware	Support Upgrade Firmware via WEB/TFTP/Console
<b>Debug</b>	
PING	Support
TRACEROUTE	Support
Telnet client	Support
Process View	Support
<b>Mechanical</b>	
L x W x H	17.6" x 11.8" x 1.7" (447mm x 300mm x 44mm)
Weight	10.6 lbs. (4.8 kg.)

HTTP://  
WWW.  
PAKEDGE  
.COM

1163 Triton Drive  
Foster City, CA 94404  
Main: 877.274.6100  
Fax: 650.685.5520  
sales@pakedge.com

**pakedgedevice&software inc.**